



MINERAL & ULTRA LOW SALT CHLORINATOR

INITIAL STARTUP/CONVERSION GUIDE FOR EXISTING SALT POOLS, EXISTING CHLORINE POOLS & NEW POOLS

1. Before installing the MineralX Chlorinator, bring the Salt TDS to the ideal level then ensure your pool water is balanced (especially pH and Alkalinity).

The ideal Salt TDS level is 1500ppm for the MineralX Chlorinator. Salt TDS levels above 2500ppm on the MineralX Chlorinator may cause damage to the unit and void the warranty. Never add salt/minerals directly to the skimmer box.

To convert an existing salt pool to a MineralX pool: Lower the Salt TDS level to 1000ppm. You may need to partially empty the pool and refill with fresh water to achieve this. Then add Pool Pro Natural Magnesium (Magnesium Chloride) according to the table below, which should bring the TDS level to 1500ppm. Allow the pump to run for 8 - 12 hours to circulate the product.

Select the pool size (in L) and add the corresponding amount (kg) of Pool Pro Natural Magnesium											
10,000L	20,000L	30,000L	40,000L	50,000L	60,000L	70,000L	80,000L	90,000L	100,000L	110,000L	120,000L
7.5kg	15kg	22.5kg	30kg	37.5kg	45kg	52.5kg	60kg	67.5kg	75kg	82.5kg	90kg

To convert an existing chlorine pool to a MineralX pool, or to start up a new pool as a MineralX pool: Add the Pool Pro MineralX Blend to raise the Salt TDS to 1500ppm. Refer to the MineralX bag instructions or scan the QR code on this flyer for more information/dosage rates. Allow the pump to run for 8 - 12 hours to circulate the product.

Note: For startup/conversion for a low salt pool instead of a mineral pool, bring the Salt TDS level to 1500ppm using pool salt.

2. After 8 - 12 hours, ensure pool water is balanced and the Salt TDS level is 1500ppm. Install and switch on the MineralX Chlorinator. Bathers can now use the pool.
3. After the initial startup/conversion, use the Pool Pro MineralX Blend to maintain the mineral setup (or use pool salt to maintain a low salt setup). Water tests should be conducted every 2 - 4 weeks.



PRODUCT CODE	DESCRIPTION
NDCMX25	Pool Pro MineralX Chlorinator 25g/hr
NDCMX35	Pool Pro MineralX Chlorinator 35g/hr
SALT10MC	Pool Pro Natural Magnesium (Magnesium Chloride) 10kg
SALT25MC	Magnesium Chloride Dead Sea Flake 25kg
SALT25MCP	Magnesium Chloride Dead Sea Pellet 25kg
SALT10MX	Pool Pro MineralX Blend Dead Sea 10kg
PC013	Magnesium Test Strips (50 strips per bottle)
SPINO4M	La Motte Spin Disc 801 Series with Magnesium (100 discs)

Note: Ideal levels for Magnesium Hardness is 600ppm - 900ppm and Calcium Hardness is 200ppm - 400ppm.

PUMPS | FILTERS | CHLORINATORS | CLEANERS | UNDERWATER LIGHTS | HEATING | ACCESSORIES | CHEMICALS | SPA PRODUCTS | SPARE PARTS



SCAN FOR MORE INFO

Simply A Better Choice

Phone Free Call: 1800 143 788 International Phone: + 61 7 3209 7884

Email: office@poolpro.com.au Web: www.poolpro.com.au